



Romaco Noack NBP 950

The Romaco Noack NBP 950 blister machine is extremely versatile and very easy to operate. With a maximum output of 500 blisters per minute and excellent OEE values, it leads the field in the mid-performance class and is ideal when frequent product changes are likely. This rotary sealing machine processes blisters both lengthwise and crosswise to the running direction.

Highlights

- Suitable for numerous blister layouts
- Fast product changes
- Ergonomic format parts
- Full compatibility of format parts with the Noack 921
- Clear structure and robust design
- cGMP compliant balcony architecture
- All common thermoformable and sealable blister foils can be processed
- Servo drives ensure absolutely reliable processes
- QuickFeed for optimised cleaning
- QuickAdjust for shorter run-in times
- Choice of dedicated optical monitoring systems
- Ready for Remote Assist
- OPC UA interface for production data acquisition (PDA)

Technical Data	Noack NBP 950
Output blisters/minute max.	500
Blister tracks max.	5
Forming cycles/minute max.	100
Cutting cycles/minute max.	200
Foil width max., in mm	214
Forming area max., in mm	170 x 204
Cutting area max., in mm	162 x 204
Forming depth max., in mm	12
Forming foil reel diameter max., in mm	700
Lidding foil reel diameter max., in mm	320
Machine dimensions (L x W x H), in mm	4,200 x 1,570 x 2,400
Weight (approx.), in kg	2,800
Remote Assist connection	Ethernet
PDA interface	OPC UA

Technical changes reserved

